


FLOORON TILE ADHESIVE TA01

Polymer Modified Normal Setting
Cementitious Floor and Wall
Tile Adhesive



**SUPERIOR BOND
STRENGTH**



**MINIMUM
SHRINKAGE**



**EASY
APPLICATION**



**LIGHTWEIGHT
FORMULA**

INTRODUCTION

FloorOn Tile Adhesive TA01 is a single-component polymer-modified normal-setting cementitious tile adhesive for general-purpose internal, clay, or ceramic floor and wall tiling. **FloorOn Tile Adhesive TA01** is most suitable for tiles that have high porosity.

Specifications:

IS 15477-2019, Type -IT.

EN 12004-1 Type -C1T.

Technical Data

Parameters	Remarks
Physical States	Cementitious Powder
Appearance	
Color	Grey
Mixed density	1.8 – 2.0 kg/litre
Open Time (IS 15477: 2019) 2kg load applied for 30 sec	~ 25 minutes
Pot Life	~ 110 minutes
Adjustment Time (IS 15477: 2019) 2kg load applied for 30sec	~ 25 minutes
Slip Resistance (T) (IS 15477: 2019)	< 0.5 mm
Tensile Adhesion at Dry Condition Type 1 (IS 15477: 2019)	Min. 0.5 N/mm ²
Shear Adhesion at Dry Condition Type 1 (IS 15477: 2019)	Min. 1.0 N/mm ²

Performance Data As per IS 15477-2019, Type-1 T

Tests	Requirements	Typical Value (Range)
Tensile Strength, N/mm ² (Dry Condition)	0.5 (minimum)	0.6 to 1.0
Shear Adhesion, N/mm ² (Dry Condition)	1.0 (minimum)	1.0 to 1.3
Slip resistance, mm, (T)	< 0.5	0.2 to 0.4

Performance Data As per EN 12004-1 Type-CIT

Tests	Requirements	Typical Value (Range)
Tensile Strength, N/mm ² (Dry Condition)	≥ 0.5	0.6 to 0.9
Tensile Strength, N/mm ² after water immersion	≥ 0.5	0.6 to 0.8
Tensile Strength, N/mm ² after Heat aging	≥ 0.5	0.7 to 1.1
Tensile Strength, N/mm ² after Freeze-Thaw cycles	≥ 0.5	0.6 to 1.0
Open Time, (>20 min) N/mm ²	≥ 0.5 (Tensile Adhesion)	0.6 to 0.9
Slip resistance, mm, (T)	< 0.5	0.2 to 0.4

METHOD OF USE

Surface Condition

Surfaces should be clean and free of dust, oil, grease, paint, tar, wax-based curing agent, primer, sealer, concrete color stains, old adhesive residues (unless otherwise recommended by Technical Services), form release agent, and any deleterious substance or debris that may prevent, reduce, or affect adhesion or performance. Surfaces must be plumb and true to within 6 mm in 10 ft (3m). Remove all excess water and standing water, if any, allowing the surface to become almost dry to provide a saturated surface-dry (SSD) condition before installing the levelling.

Mixing

20–30% water or 4-6 litres of water for 20 kg of powder in a clean mixing vessel. Mix with a suitable mechanical stirrer or slow-speed drills (100–400 rpm). and mix until a uniform lump-free consistency is obtained.

How to apply

- Apply the tile adhesive using the notched trowel to create thick ridges.
- Apply the tile adhesive in upward, sweeping motions.
- Fix the tile carefully.
- Push your tile into the adhesive and give it a slight twist. This will bed it securely onto the wall and reduce the amount of air that can sit between the tile and wall surface.
- Use a rubber mallet to tap the tile down so the adhesive grips. Now, repeat until the wall, floor, or substrate is complete.
- Repeat this with the next tile, using spacers to separate the tiles as you go.
- Adjust the tile within 25 minutes if required.
- Water should not be added to try and regain its characteristics when tile adhesive crosses its pot life.

Coverage

A 20kg bag of **FloorOn Tile Adhesive TA01** will cover approximately 5 to 6 square meters of tiles at a bed thickness of 3mm (this is how thick the layer of adhesive is). The bed layer can be up to 12mm if needed.

Features and Advantages

- It is a grey cement-based polymer-modified adhesive.
- For fixing all types of ceramic tiles for interior substrates, e.g., floors, kitchens, bathroom walls, corridors, lounges, meeting rooms, halls, etc.
- Fast Installation.
- Single component, add water to it, and it is ready to use.
- High bonding strength between substrate and tiles
- Self-curing adhesive.
- Fast drying
- Safe to use.
- Slip resistance with a longer pot life.
- Excellent adhesion properties
- It complies with IS 15477:2019, IS 15447:2004, and EN 12004.

Precautions

- The floor or substrate to which tile adhesive has to be applied should be flat and in SSD (wet outside and dry inside).
- The uneven or extremely rough surfaces, if any, should be levelled with cement mortar or PAMR repair mortar.
- Keep out of reach of children, wear gloves, and wear safety PPE at the time of use.
- Never mix the dried mortar with water to use again.

Shelf Life & Storage

12 months from the date of manufacturing. The suitable ambient temperature is 5°C to 40°C. Keep the material in a dry place and avoid contact with moisture.

Packing

20/25/50 kg in HDPE bags.

Other Products Categories available

PAMR brings you the widest range of Construction Chemicals



WATERPROOFING
COMPOUND




REPAIR MORTAR



TILE & STONE
FIXING SOLUTIONS



ADHESIVE &
SEALANTS



PROTECTIVE
COATING



GROUTS &
GROUTING
COMPOUNDS



FLOOR
HARDENERS



CONCRETE
ADMIXTURES

The information contained in this technical data sheet is given to the best of our knowledge and the results from extensive testing in order to remain as objective as possible. However, in any case it cannot be considered as a warranty involving our liability in case of misuse or any different use of our products from the “Application” paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Consult the latest update of the technical data sheet on our website www.pamrindustries.com